CONTRACTOR Product SPEC (Silmee Bartype Lite)

©TDK

Product name	Silmee Bar type Lite
•Model number	TK010HM00
•Sensor	Acceleration sensor
	Pulse sensor
	ECG sensor
	Temperature sensor
 Wireless communication method 	Conforms to Bluetooth Ver. 4.0 (Class 2)
Movinum Witchess communication distance	(protocol depends on the firmware)Line-of-sight distance: Approx. 10 m
Maximum Wireless communication distance	(depends on the operating environment)
•Wireless frequency band	2.4-GHz band (2.4000 GHz to 2.4835 GHz)
Wheless hequency band	
Wired communication method	USB 2.0 Full Speed
Power supply	Internal lithium polymer battery
Continuous operating time	Approx. 24 hours (depending on the operating conditions) *On-line Approx. 8 hours, Off-line Approx. 24hours
•Charge time	Approx. 2hours
•Number of Charges	Use this product about once per day as a rule
•External dimensions	64 (width) $ imes$ 28 (depth) $ imes$ 9.6 (thickest part) mm
	(excluding protrusions)
·Weight	Approx. 14.0 g (including battery)
•Operating environment temperature/humidity	Ambient temperature range: 10°C to 40°C at a relative
	humidity of 30% to 90% (without condensation)
•Waterproofness	IPX5/7
•Memory	Approx. 16 MB (up to 14 fi les)

Copyright[©] 2016 TDK Corporation. All rights reserved.

TDK Corporation IoT system BU June, 2016 - 0 -