## ZBVB33

Light block, Harmony XB4, Harmony XB5, green for head Ø22 mm integral LED 24 V faston connector





# Main

Harmony XB4 Harmony XB5	
Light block	
ZBV	
5	
Faston connector 1 x 6.35 mm Faston connector 2 x 2.8 mm	
Steady	
Protected LED	
Integral LED	
Direct	
Green	
24 V AC/DC 50/60 Hz	

### Complementary

Net Weight	0.04 lb(US) (0.017 kg)	
Supply voltage limits	19.230 V DC	
	21.626.4 V AC	
Current Consumption	18 mA	
Service life	100000 h at rated voltage and 25 °C	
Surge withstand	1 kV IEC 61000-4-5	
Mounting of block	Front mounting	
Electrical composition code	M1	
	M2	
	M3	
	M4	
	M5	
	M6	
	M10	
	MF1	
	P1	
	P2	
	PF1	

### Environment

Protective treatment	TH
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Ambient air temperature for operation	-40158 °F (-4070 °C)
IP degree of protection	IP20 IEC 60529
Standards	EN/IEC 60947-5-1 UL 508 EN/IEC 60947-5-5 EN/IEC 60947-1 JIS C8201-5-1 CSA C22.2 No 14 EN/IEC 60947-5-4 JIS C8201-1
Resistance to fast transients	2 kV IEC 61000-4-4
Resistance to electromagnetic fields	9.14 V/m (10 V/m) IEC 61000-4-3

Resistance to electrostatic discharge	6 KV on contact (on metal parts) IEC 61000-4-2 8 kV in free air (in insulating parts) IEC 61000-4-2
Electromagnetic emission	Class B IEC 55011
[Us] rated supply voltage	24 V
Ordering and shipping details	
Category	22469 - PUSHBUTTON,22MM ACCESSORIES-NEW
Discount Schedule	CS2
GTIN	3389110816600
Nbr. of units in pkg.	1
Package weight(Lbs)	0.35 oz (10 g)
Returnability	No
Country of origin	FR
Packing Units Unit Type of Package 1	PCE
Package 1 Height	2.20 in (5.6 cm)
Package 1 width	1.73 in (4.4 cm)
Package 1 Length	2.13 in (5.4 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	5
<u> </u>	1.90 oz (54 g)
Package 2 Weight	
Package 2 Weight Package 2 Height	2.20 in (5.6 cm)
Package 2 Weight	2.20 in (5.6 cm) 1.73 in (4.4 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EPEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	

#### Contractual warranty

	•	
Warranty	18	B months